




## PLACA



**Aceros Alianza**  
SERVICIO PERSONALIZADO



**NORMA: ASTM A – 6; ASTM A – 36; ASTM A - 572**

MEDIDAS		PESO REÓRICO EN KILOGRAMOS							
		ESPESORES							
PIES	METROS	3/16"	1/4"	5/16"	3/8"	7/16"	1/2"	9/16"	5/8"
		4.76 mm	6.35 mm	7.93 mm	9.52 mm	11.11 mm	12.7 mm	14.28 mm	15.87 mm
3 X 6	0.91 x 1.83	63	83	104	125	146	167	188	209
3 X 8	0.91 x 2.44	83	111	139	167	195	223	250	278
3 X 10	0.91 x 3.05	104	139	174	209	243	278	313	348
3 X 20	0.91 x 6.10	209	278	348	417	487	556	626	696
4 X 8	1.22 x 2.44	111	148	185	223	260	297	334	371
4 X 10	1.22 x 3.05	139	185	232	278	325	371	417	464
4 X 20	1.22 x 6.10	278	371	464	556	649	742	935	927
5 X 10	1.52 x 3.05	173	231	289	347	404	462	520	578
5 X 20	1.52 x 6.10	347	462	578	693	809	924	1040	1155
6 X 10	1.83 x 3.05	209	278	348	417	487	556	626	696
6 X 20	1.83 x 6.10	417	556	696	835	974	1113	1252	1391
8 X 10	2.44 x 3.05	278	371	464	556	649	742	835	927
8 X 20	2.44 x 6.10	556	742	927	1113	1298	1484	1669	1855
Kg/m <sup>2</sup>		37.386	49.848	62.309	74.771	87.233	99.695	112.157	124.619
Lb/Pie <sup>2</sup>		3.473	4.631	5.789	6.946	8.104	9.262	10.420	11.577

**NORMA: ASTM A – 6; ASTM A – 36; ASTM A - 572**

MEDIDAS		PESO REÓRICO EN KILOGRAMOS							
		ESPESORES							
PIES	METROS	11/16"	3/4"	7/8"	1"	1 1/2"	2"	2 1/2"	3"
		17.46 mm	19.05 mm	22.22 mm	25.40 mm	38.10 mm	50.80 mm	63.50 mm	76.20 mm
3 X 6	0.91 x 1.83	230	250	292	334	501	668	835	1002
3 X 8	0.91 x 2.44	306	334	390	445	668	890	1113	1335
3 X 10	0.91 x 3.05	383	417	487	556	835	1113	1391	1669
3 X 20	0.91 x 6.10	765	835	974	1113	1669	2226	2782	3339
4 X 8	1.22 x 2.44	408	445	519	594	890	1187	1484	1781
4 X 10	1.22 x 3.05	510	556	649	742	1113	1484	1855	2226
4 X 20	1.22 x 6.10	1020	1113	1298	1484	2226	2968	3710	4452
5 X 10	1.52 x 3.05	636	693	809	924	1387	1849	2311	2773
5 X 20	1.52 x 6.10	1271	1387	1618	1849	2773	3697	4622	5546
6 X 10	1.83 x 3.05	765	835	974	1113	1669	2226	2782	3339
6 X 20	1.83 x 6.10	1530	1669	1948	2226	3339	4452	5564	6677
8 X 10	2.44 x 3.05	1020	1113	1298	1484	2226	2968	3710	4452
8 X 20	2.44 x 6.10	2040	2226	2597	2968	4452	5935	7419	8903
Kg/m <sup>2</sup>		137.081	149.543	174.466	199.390	299.085	398.780	498.475	598.170
Lb/Pie <sup>2</sup>		12.735	13.893	16.208	18.524	27.786	37.048	46.310	55.572

Basada en el peso específico del acero: P=7850 Kg/m<sup>3</sup>

En rollo, disponible en anchos de 3' 4' 5' y 6'

En existencia en acero A-36, A 572 G50

**SOBRE PEDIDO**